

Options



Description

(1) Metal cover diam.280 mm

Outlet pressure

406 bar (air pressure at 7 bar)

Pressure ratio

58:1

Technology

Piston dual action

Flow rate

900 g/min (for air pressure 6 bar)

BSPP male thread

Grease outlet : G 1/4

Operating pressure

3 to 7 bar

BSPP female thread

Air inlet : G 1/4

Description

Reference

EPG CV20

Description

(1) Metal cover diam.280 mm

Reference	Description
EPG CV30	(1) Metal cover diam. 320 mm
EPG CV60	(1) Metal cover diam. 385 mm
EPG CV65	(1) Metal cover Ø 380 to 410 mm
EPG MB20	(2) Sealing diaphragm Ø 240/260mm
EPG MB30	(2) Sealing diaphragm Ø 270/290 mm for EPG KR30
EPG MB31	(2) Sealing diaphragm for drum Ø 280/300 mm
EPG MB34	(2) Sealing diaphragm Ø 300/330 mm
EPG MB60	(2) Sealing diaphragm Ø 335/360 mm for EPG KR60
EPG MB65	(2) Sealing diaphragm Ø 370/400mm
EPG TC414	(3) Rubber hose 4 m
EPG TC614	(3) Rubber hose 6 m
EPG TC214	(3) Rubber hose for connecting pump to reel
EPG RT14	Sealing coupling
EPG SW14	(4) Universal joint sealing coupling
EPG PG	Carrying handle
EPG VS30	(5) 30 mm bolt to hold pump in drum

Reference	Description
EPG CA20	(6) Transport cart for 12/20 kg drums
EPG CAN60	(6) Transport cart for 20/60 kg